

# SERIES 2 TAPPING BANDS



## Design Advantage

- Quick and easy installation
- Positive stop to prevent overtightening
- Superior corrosion protection

### Technical Detail

Range	DN100 to DN300
Pressure	PN16
Temperatures	40°C
Applications	Potable Water, Recycled Water
Pipe Material	PVC-M, PVC-O, Ductile Iron, Asbestos Cement
Colours	Blue and Purple



### Compliance

- AS/NZS4793 Licence ACS 3004
- WSAA PA 1018



### SUITABLE FOR - PVC-M, PVC-O, DUCTILE IRON, ASBESTOS CEMENT PIPE

DN	OD (mm)	E-LIP SEAL OR O-RING	TAPPING SIZE (BSP)				
			20mm (3/4")	25mm (1")	32mm (1 1/4")	40mm (1 1/2")	50mm (2")
100	122	E-Lip	✓	✓	✓	✓	✓
150	177	E-Lip	✓	✓	✓	✓	✓
200	232	E-Lip	✓	✓	✓	✓	✓
225	259	E-Lip	✓	✓	✓	✓	✓
250	286	E-Lip	✓	✓	✓	✓	✓
300	345	E-Lip	✓	✓	✓	✓	✓



www.daemco.com.au  
1800 323 626  
enquiries@daemco.com.au



www.daemco.com.au



VALVES



COUPLINGS



ACCESSORIES



PE DI FITTINGS



COVERS



BANDS

65 Assembly Drive, Tullamarine VIC 3043  
1800 323 626 | [enquiries@daemco.com.au](mailto:enquiries@daemco.com.au)

Follow us on **LinkedIn**

©Copyright 2018. All Rights Reserved. Daemco Australia reserve the right to change designs and specifications without notice, warranties for suitability for use, liability or loss, damage or costs incurred relating to this information is excluded.