

# DUCTILE IRON BLANK FLANGES



## Design Advantage

- FBE coated
- Blank and Tapped
- Lightweight



## Technical Detail

**Range** DN80 to DN375  
\*Larger sizes upon request

**Pressure** PN16

**Material** Ductile Iron FBE Coated

**Applications** Potable Water, Recycled Water,  
Waste Water and Sewer

## Compliance

- AS/NZS 2280 Licence WM-022892 and OMK30047
- WSAA PS 1805



DN	BLANK	TAPPED (mm) †
80	✓	25, 50
100	✓	25, 50 & Off-Set 50
150	✓	25, 50
200	✓	50
225	✓	50
250	✓	50
300	✓	50
375	✓	50

† Other tapplings upon request.



www.daemco.com.au



VALVES



COUPLINGS



ACCESSORIES



PE DI FITTINGS



COVERS



BANDS

65 Assembly Drive, Tullamarine VIC 3043  
1800 323 626 | [enquiries@daemco.com.au](mailto:enquiries@daemco.com.au)

Follow us on **LinkedIn**

©Copyright 2018. All Rights Reserved. Daemco Australia reserve the right to change designs and specifications without notice, warranties for suitability for use, liability or loss, damage or costs incurred relating to this information is excluded.