

EPDM VALVE CONES

Design Advantage

EPDM cones are used to replace original braided packings in water valve stuffing boxes. The rubber cones are simpler to install and have proved to last much longer than packings, which are also prone to break-down with particles being washed into the water system.

As a flexible rubber component, this design of seal ensures constant pressure to form a water-tight seal even in worn valves and can help prolong valve use, especially useful in emergency situations where replacement hardware cannot be quickly fitted.



Technical Detail

Size #4 to #55

Material EPDM

Applications Potable and Recycled Water



SIZE	OVERALL HEIGHT	INSIDE Ø	VALVE STEM Ø
#4	24	22.2	20mm/¾"
#6	31	25	25mm/1"
#7	45	32	31mm/1.1/4"
#8	30	28	28mm/1.1/16"
#9	50	34	34mm/1.3/8" Deep
#10	25.5	31.5	31mm/1.1/4"
#11	71	41	41mm/1.5/8"
#12	32	34	34mm/1.3/8"
#14	36	38	38mm/1.1/2"
#16	36	40	40mm/1.9/16"
#18	40	43.6	44mm/1.3/4"
#48	54	48	48mm/1.7/8"
#55	43	54	54mm/2"

* Standard sizes shown, others upon request.



www.daemco.com.au



VALVES



COUPLINGS



ACCESSORIES



PE DI FITTINGS



COVERS



BANDS

65 Assembly Drive, Tullamarine VIC 3043
1800 323 626 | enquiries@daemco.com.au

Follow us on **LinkedIn**

©Copyright 2018. All Rights Reserved. Daemco Australia reserve the right to change designs and specifications without notice, warranties for suitability for use, liability or loss, damage or costs incurred relating to this information is excluded.